

THAT WHICH IS CLAIMED:

1. A mold frame for a display device
comprising:
means for receiving a display device light
source;
5 means for receiving a display device light
guide; and
means for fixing the light guide, the fixing
means including at least one rounded corner.

2. A mold frame according to Claim 1
wherein the fixing means comprises a groove including
at least one rounded corner.

3. A mold frame according to Claim 1:
wherein the fixing means includes a first
corner, and a second corner which is remote from the
means for receiving a display device light source
relative to the first corner; and
5 wherein the first corner is angled and the
second corner is rounded.

4. A mold frame according to Claim 2
wherein the groove is free of sharp angles.

5. A light guide panel for a display device
comprising:
a light guide plate; and
a light guide projection which extends from
5 the light guide plate, the light guide projection
including at least one rounded corner.

6. A light guide panel according to Claim 5
wherein the light guide projection includes a first
corner and a second corner; and
wherein the first corner is angled and the
5 second corner is rounded.

sub
a.

sum
a2

08847017.050197

9

7. A light guide panel according to Claim 5 wherein the light guide projection is free of sharp angles.

8. A backlight unit for a display device comprising:

a mold frame which includes a groove having at least one rounded corner; and

a light guide panel mounted on the mold frame, including a light guide projection mounted in the groove and having at least one rounded corner corresponding to the at least one rounded corner of the mold frame groove.

9. A backlight unit according to Claim 8 further comprising:

a light source mounted on the mold frame, in spaced apart relation from the light guide panel;

wherein the mold frame groove and the light guide panel both include a first corner, and a second corner which is remote from the light source relative to the first corner; and

wherein the first corner is angled and the second corner is rounded.

10. A backlight unit according to Claim 8 wherein the groove and light guide projection are both free of sharp angles.

11. A flat panel display device comprising:
a mold frame which includes a groove having at least one rounded corner;

a light guide panel on the mold frame, including a light guide projection mounted in the groove and having at least one rounded corner

08847017 050197

See
Q3
5

5

10

5

corresponding to the at least one rounded corner of the mold frame groove;

10 a light source on the mold frame, in spaced apart relation from the light guide panel; and
 an array of display elements on the light guide panel, opposite the mold frame.

12. A flat panel display device according to Claim 11 further comprising a diffuser between the light guide panel and the array of display elements.

13. A flat panel display device according to Claim 12 further comprising a printed circuit board on the mold frame, the printed circuit board including a plurality of integrated circuits which are electrically
5 connected to the array of display elements.

14. A flat panel display device according to Claim 11:

 wherein the mold frame groove and light guide panel both include a first corner, and a second corner
5 which is remote from the light source relative to the first corner; and

 wherein the first corner is angled and the second corner is rounded.

15. A flat panel display device according to Claim 11 wherein the groove and light guide projection are both free of sharp angles.

add
64

08847017.050197